

AMILO Display SL 3230T

23 Inch LCD widescreen Display

Issue September 2008

Pages 2

The AMILO Display SL 3230T offers Full HD picture (1080P) for home office and entertainment. With the large size and the 2 HDMI interfaces the AMILO Display SL 3230T is the center to enjoy all pc, gaming and video content. Due to its extremely slim and stylish design, the AMILO Display SL 3230T fits perfectly into your home environment.

Highlights

- 16:9 widescreen display
- Full HD (1080P) resolution 1920 x 1080
- 2 HDMI 1.3 interfaces (incl. HDCP)
- Stylish glossy black design
- Theme mode for optimized picture
- Aspect ratio conversion

Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent color purity
- Well balanced brightness uniformity
- Excellent Advanced Contrast Ratio (10,000:1)
- Space saving design

Technical highlights

- 23" (58.4cm) LCD widescreen display
- Excellent contrast (ACR) 10,000:1
- Brightness 300 cd/m²
- Fast response time (typ.) 5 ms
- Internal power supply

Reliability

- Lifetime Extender
- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



RESPONSE TIME



ACR CONTRAST



HIGH DEFINITION



HDCP



SPEAKER

Visible screen diagonal	23 inch (58.4 cm)
Resolutions	
Pixels	1920 x 1080
Pixels expanded	1280 x 768
Picture size	509.2 x 285.4 mm
Colors	16.7 million
Pixel Pitch	0.266 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	56 - 76 Hz
Brightness (typical)	300 cd/m²
Advanced Contrast Ratio	10,000:1
Viewing angle at CR > 5:1	
Horizontal	170°
Vertical	170°
Response time (typical)	5 ms
Plug and Play	VESA DDC/ CI
Setting options	
Menu language (16 languages)	
Power saving mode with Lifetime Extender	
Theme Mode	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Factory recall setting	
OSD Language	
English, German, French, Italian, Spanish, Portuguese,	
Swedish, Dutch, Finnish, Danish, Norwegian,	
Russian, Polish, Hungarian, Czech and Turkish	
Base	
Tilt angle	-5° / +15°
Video input	2 x HDMI (1.3), 1x D-SUB
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output	2 W (L) + 2 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw (EPA)	
EPA 'On Mode'	28 W
EPA 'Max.'	< 55 W
Stand by	<0.5 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	412 x 543.2 x 214.9mm
Weight (Monitor only)	4.6 kg
Reliability	
MTBF (demonstrated)	50,000 h
Lifetime of LCD backlight	30,000 h
(brightness > 50 % of original brightness)	
Compliance with standards	
Product safety	EN60950
Ergonomics	ISO13406-2
	(Pixel fault class II)
Radiation immunity and	CE certification according
RFI suppression	to EC Directive
	2004/108/EEC
	(EN55022/B, EN55024
	EN61000-3-2/-3)
Ecology	RoHS, IT-Eco-declaration,
	Energy Star (EPA 4.1)
Accessories	
Power cable (1.8 m)*	1x wall socket
	(Euro-Schuko-Type CEE7)
Data cable (1.8 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5 mm stereo phone jack
* detachable on display	
Special features	Standardized mounting
	interface according
	VESA FPMPI (100 mm)
	Kensington Lock
Order code	S26361-K1303-V181
EAN	4333643806149
SAP order name	AMILO LSL 3230T